



B196

BahcoFit VDE Insulated Slotted Screwdrivers with Multi-Component Handle 2.5 mm-12 mm



PRODUCT DETAILS

- Insulated VDE Screwdriver for slotted head screws
- For work on live equipment up to 1000 V, high quality blade insulation moulded directly onto the blade
- Black oxide tip for higher accuracy
- Two-component handle with vertical grooves and large soft-grip area for comfortable grip and high torque transfer
- Handle made with over 75% rubber
- Anti-slip surface
- Permanent symbol and markings on the handle for quick identification of the tip
- Integrated hanging hole
- Blade made of high-performance alloy steel
- Individually inspected and manufactured according to IEC 60900, tested in a water bath at 10000 V
- Standards: ISO 2380, DIN 5264
- SB = Retail packed on a plastic hanger



Follow the Fish!



PRODUCT ATTRIBUTES

Product							
B196.025.075	0.4 mm	2.5 mm	75 mm	24.5 mm	95 mm	170 mm	36 g
B196.030.100	0.5 mm	3 mm	100 mm	24.5 mm	95 mm	195 mm	38 g
B196.035.100	0.6 mm	3.5 mm	100 mm	24.5 mm	95 mm	195 mm	38 g
B196.040.100	0.8 mm	4 mm	100 mm	24.5 mm	95 mm	195 mm	38 g
B196.055.125	1 mm	5.5 mm	125 mm	24.5 mm	95 mm	220 mm	66 g
B196.065.150	1.2 mm	6.5 mm	150 mm	30 mm	105 mm	255 mm	90 g
B196.080.175	1.2 mm	8 mm	175 mm	34 mm	117 mm	292 mm	140 g
B196.100.200	1.6 mm	10 mm	200 mm	34 mm	117 mm	317 mm	189 g
B196.120.200	2 mm	12 mm	200 mm	34 mm	117 mm	317 mm	205 g
SB196.025.075	0.4 mm	2.5 mm	75 mm	24.5 mm	95 mm	170 mm	40 g
SB196.030.100	0.5 mm	3 mm	100 mm	24.5 mm	95 mm	195 mm	42 g
SB196.035.100	0.6 mm	3.5 mm	100 mm	24.5 mm	95 mm	195 mm	42 g
SB196.040.100	0.8 mm	4 mm	100 mm	24.5 mm	95 mm	195 mm	42 g
SB196.055.125	1 mm	5.5 mm	125 mm	24.5 mm	95 mm	220 mm	70 g
SB196.065.150	1.2 mm	6.5 mm	150 mm	30 mm	105 mm	255 mm	94 g
SB196.080.175	1.2 mm	8 mm	175 mm	34 mm	117 mm	292 mm	144 g
SB196.100.200	1.6 mm	10 mm	200 mm	34 mm	117 mm	317 mm	193 g
SB196.120.200	2 mm	12 mm	200 mm	34 mm	117 mm	317 mm	209 g

Follow the Fish!

