



B199

BahcoFit VDE Insulated Nut Drivers with Multi-Component Handle 5.5 mm-13 mm



PRODUCT DETAILS








- Insulated VDE Screwdriver with slim bore for hexagon head screws, bolts and nuts
- For work on live equipment, up to 1000 V, high quality blade insulation moulded directly onto the blade
- Two-component handle with vertical grooves and large soft-grip area for comfortable grip and high torque transfer
- Handle made with over 75% rubber
- Anti-slip surface
- Permanent symbol and markings on the handle for quick identification of the tip
- Integrated hanging hole
- Blade made of high-performance alloy steel
- Individually inspected and manufactured according to IEC 60900, tested in a water bath at 10000 V
- SB = Retailed packed on a plastic hanger



Follow the Fish!



PRODUCT ATTRIBUTES

Product							
B199.055.125	5.5 mm	11x30 mm	125 mm	30 mm	105 mm	230 mm	91 g
B199.060.125	6 mm	12x30 mm	125 mm	30 mm	105 mm	230 mm	127 g
B199.070.125	7 mm	14x30 mm	125 mm	34 mm	117 mm	242 mm	127 g
B199.080.125	8 mm	15x30 mm	125 mm	34 mm	117 mm	242 mm	142 g
B199.090.125	9 mm	16x30 mm	125 mm	34 mm	117 mm	242 mm	142 g
B199.100.125	10 mm	17x30 mm	125 mm	34 mm	117 mm	242 mm	142 g
B199.110.125	11 mm	17x30 mm	125 mm	34 mm	117 mm	242 mm	181 g
B199.120.125	12 mm	20x30 mm	125 mm	34 mm	117 mm	242 mm	182 g
B199.130.125	13 mm	21x30 mm	125 mm	34 mm	117 mm	242 mm	183 g
SB199.055.125	5.5 mm	11x30 mm	125 mm	30 mm	105 mm	230 mm	95 g
SB199.060.125	6 mm	12x30 mm	125 mm	30 mm	105 mm	230 mm	131 g
SB199.070.125	7 mm	14x30 mm	125 mm	34 mm	117 mm	242 mm	131 g
SB199.080.125	8 mm	15x30 mm	125 mm	34 mm	117 mm	242 mm	146 g
SB199.090.125	9 mm	16x30 mm	125 mm	34 mm	117 mm	242 mm	146 g
SB199.100.125	10 mm	17x30 mm	125 mm	34 mm	117 mm	242 mm	146 g
SB199.110.125	11 mm	17x30 mm	125 mm	34 mm	117 mm	242 mm	185 g
SB199.120.125	12 mm	20x30 mm	125 mm	34 mm	117 mm	242 mm	186 g
SB199.130.125	13 mm	21x30 mm	125 mm	34 mm	117 mm	242 mm	187 g

